

Benefits

- Easy to mobilise due to its light weight
- Minimises operational footprint
- Existing well services personnel can deploy
- Remote support available
- Minimal maintenance man-hour requirements
- Small, agile fleet enabling faster intervention

Features

- Lowest friction coefficient in the market
- Modular
- Multiple Wheel Sizes per chassis
- Faster Deployment and retrieval to reduce rig time
- Extended Target Depth reach
- Quick re-dress to reduce rig time
- Eliminate failure with patented wheel retention
- Secure **GARD U-line™** connection for impact loads

Applications

- Production Logging Tool
- Cement Bond Log
- Perforating
- Caliper
- Pipe Recovery
- Camera
- Inflatable plugs
- Drifting
- Memory Gauge
- Gas Lift Remediation
- Plugging
- Sliding Side Door Manipulation


Specifications

WR02 Series Specifications						
Size (in)	Weight (kg)	Length	Nominal Tubing Size	ID	Max Tool OD Conveyed	Connection Type
2.200	11.598				1.875	
2.300	11.654					
2.400	11.713				2.000	
2.500	11.774				2.125	
2.530	11.792			2.750	2.430	
2.600	11.837				2.250	
2.625	11.853					
2.650	11.870					
2.675	11.886					
2.700	11.903					
2.725	11.920		3 1/2			
2.750	11.937				2.650	
2.775	11.954					
2.800	11.971			2.922		
2.825	11.989					
2.850	12.008					
2.875	12.024					
2.900	12.042			2.992		
2.925	12.060					
2.950	12.078			3.068		
2.975	12.097					
3.000	12.115					
3.025	12.134					
3.050	12.153					
3.075	12.172					
3.100	12.191					
3.125	12.210					
3.150	12.230					
3.175	12.250					
3.200	12.269			3.476		
3.225	12.289		4			
3.250	12.309				3.150	
3.275	12.330					
3.300	12.350					
3.325	12.371					
3.350	12.391					
3.375	12.412					
3.400	12.433					
3.425	12.455			3.548		
3.450	12.476					
3.475	12.497					
3.500	12.519				3.400	
3.525	12.541					
3.550	12.563					
3.575	12.585		4.5	3.958		
3.600	12.607					
3.625	12.630					
3.650	12.652					


Connections available to meet customer specifications




2530.WR02 in 3.5" tubing
(0.375" wall thickness)




2750.WR02 in 3.5" tubing
(0.289" wall thickness)



3000.WR02 in 4" tubing
(0.262" wall thickness)



3250.WR02 in 4" tubing
(0.226" wall thickness)



3500.WR02 in 4.5" tubing
(0.271" wall thickness)